

**JUAL HT ICOM, MOTOROLA, YAESU, KENWOOD, JUAL HT, DEALER RIG, TORIPHONE, GARMIN**

*Washupito's Tiendita*

**IC-T70A / IC-T70E DUAL BAND**

Frequency range (unit: MHz)	∆
Tx	144-148, 420-450*1
Rx <sup>∆</sup>	136-174, 400-479*1
∆	*1 guaranteed 144-148 MHz, 440-450 MHz
Type of emissions	F2D/F3E (FM)
Number of memory ch.	302 (incl. 50 scan edges and 2 call)
Antenna impedance	50 ∆ (SMA)
Power supply	7.2V DC (with BP-264)
External DC power	10-16V DC
Battery cells	6-10V DC
Frequency stability	∆±2.5 ppm -20∆°C to +60∆°C basis of 25∆°C
Current drain (at 7.2V DC or 13.5V DC)	Tx High (UHF/VHF) 1.7 A/2.1 A typical Rx Max. audio Less than 450mA (internal SP, 16∆ <sup>©</sup> )
(VHF/UHF, typical)	∆ Less than 300mA (External Sp, 8∆ <sup>©</sup> )
∆	Stand-by ∆ ∆ ∆ ∆ ∆ ∆ ∆ ∆ ∆ ∆ ∆ Less than 90mA
∆	Power saved ∆ ∆ Less than 40mA (1:8 duty
Operating temperature range	-20∆°C to +60∆°C
∆	-4∆°F to +140∆°F
Dimensions	58(W) ∆— 111(H) ∆— 30(D) mm
(projections not included)	2 <sup>9</sup> ∆ <sup>•</sup> <sub>32</sub> (W) ∆— 4 <sup>3</sup> ∆ <sup>•</sup> <sub>8</sub> (H) ∆— 1 <sup>3</sup> ∆ <sup>•</sup> <sub>16</sub> (D) in

[∆ Vendor Information](#)