

JUAL HT ICOM, MOTOROLA, YAESU, KENWOOD, JUAL HT, DEALER RIG, TORIPHONE, GARMIN

Washupito's Tiendita

IC-T70A / IC-T70E DUAL BAND

Frequency range (unit: MHz)	Â
Tx	144-148, 420-450*1
RxÂ	136-174, 400-479*1
Â	*1guaranteed 144-148 MHz, 440-450 MHz
Type of emissions	F2D/F3E (FM)
Number of memory ch.	302 (incl. 50 scan edges and 2 call)
Antenna impedance	50 Î© (SMA)
Power supply	7.2V DC (with BP-264)
External DC power	10-16V DC
Battery cells	6-10V DC
Frequency stability	Â±2.5 ppm -20Â°C to +60Â°C basis of 25Â°C
Current drain (at 7.2V DC or 13.5V DC)	Tx High (UHF/VHF) 1.7 A/2.1 A typical Rx Max. audio Less than 450mA (internal SP, 16Î©)
(VHF/UHF, typical)	Â Less than 300mA (External Sp, 8Î©)
Â	Stand-byÂ Â Â Â Â Â Â Â Â Â Â Â Â Less than 90mA
Â	Power savedÂ Â Less than 40mA (1:8 duty)
Operating temperature range	-20Â°C to +60Â°C
Â	-4Â°F to +140Â°F
Dimensions (projections not included)	58(W) Ã— 111(H) Ã— 30(D) mm 2 ⁹ â„ _{„32} (W) Ã— 4 ³ â„ _{„8} (H) Ã— 1 ³ â„ _{„16} (D) in

[Vendor Information](#)